

# Compact Worker with 4 multifunction hobs MS-I-Worker M, 4×7kW

Item no. 203896



## Top quality «à la carte» range

A top quality range for small restaurants. Maximum flexibility in application. Ideal for «à la carte» cooking as well as for set menu dishes. Four induction hobs controlled independently, designed for everyday use.

# Benefits that are spot on

- Energy saving increased by 50 to 85% as compared to conventional cooking technology
- Minimum heat emission levels allow for an optimum kitchen working environment
- Extremely quick boiling times. Maximum heat output is achieved within just a few seconds.
- Freely adjustable, highly precise energy metering for perfectly cooked food
- Maximum power density per cm<sup>2</sup> at pan base

- Pan type detection (material, size, power consumption properties)
- 2-zone pot detection and temperature monitoring
- Automatic fan monitoring

#### **Equipment**

°CelsiusClass multi-mode controller Multi-segment digital displays Ultra-strong ceramic glass Rear upstand CU100 Main switch with indicator light

### Substructure

Hygiene substructure with pan tray table Star induction base CNS plinth 100 mm

# Technology that is globally unique

The MENU SYSTEM induction technology





# Multi-mode controller

Control with freedom for cooks.



# **Blueline induction**

Energy and temperature management consistent every time.



# **Star induction base**

The best cooking performance thanks to superior technology.

## MS-I-Worker M Item no. 203896





# Top quality «à la carte» range

4 Multifunction induction hobs 7 kW each

The multifunction hob is ideal for cooking with two to four pans. Thanks to the capacity and high power density of the coil, it's a perfect choice for both production and finishing.


- For 4 saucepans measuring 16 cm or a cooking pot up to 38 cm
- Effective field ø 340 × 360 mm
- 2-zone pot detection and temperature monitoring


# Design

- Hob made from high-quality glass-ceramic material
- Complete housing made from solid stainless steel (Chromium nickel steel 1.4301)
- Removable, easy to clean grease filter
- Massive CNS plinth
- Continuously variable, electronic power control for highly precise energy metering
- One-handed operation using 4 multi-mode controllers
- Control and power electronics resistant to power supply fluctuations

# Technical data

Dimension	800 × 800 × 900 mm
Glas dimension	2 × 360 × 360 mm
Connected load	4 × 7 kW
	3×400-440 VAC
	50/60 Hz
Heat emission	latent 1960 W
	sensible 2240 W
Plug	CEE 32
Cable length	2.5 m
Weight	136 kg





# **Safety instructions**

The exhaust air must be allowed to escape unobstructed. The grease filter must be cleaned regularly.



The experience MENU SYSTEM has gained as the leader of the induction cooking suite market flows directly into the design and development of our standalone appliances. Accordingly, our standalone appliances provide the ideal response to the needs of professionals.



# **Quality guaranteed**

Our manufacturer's warranty vouches for the quality of our products. Depending on country and region, service and warranties are looked after either by MENU SYSTEM directly or by our authorised partners.



### Made in Switzerland

With MENU SYSTEM, induction technology, electrical technology and metal-worked components all come from a single source. The high degree of vertical integration guarantees full control based on quality and expertise. For MENU SYSTEM, «Made in Switzerland» isn't just a label—it's a philosophy and a living reality.